

*“Because you’re not just a pro,
you’re an expert.”*



- IN STOCK - Ready to Ship
- High Strength - No Worry!
- UL Rated 7.5" - 48" Available

FEATURES

- Material: UL approved nylon PA66
- Flammability: UL94V-2
- Op Temps: -40°C to 85°C
- Rating: UL 181B-C (Mechanical fasteners for use with flexible air ducts & air connectors)
- Design: For use with flexible ducts in HVAC application
- Certifications: RoHS certified & CE certified
- 500 Case Quantity (42 cases per pallet)
- 500 Pieces per Bag (10 bags per case)
- 36" and 48" Cable Ties – 175lb rating
- 7.5" and 11" Cable Ties – 50lb rating

XP#	DESCRIPTION	COLOR	COUNT
XCT48N	Cable Tie - 48" - 175lb	Natural	50ct
XCT36N	Cable Tie - 36" - 175lb	Natural	50ct
XCT11N	Cable Tie - 11" - 50lb	Natural	100ct
XCT7N	Cable Tie - 7.5" - 50lb	Natural	100ct
XCT48BL	Cable Tie - 48" - 175lb	Black	50ct
XCT36BL	Cable Tie - 36" - 175lb	Black	50ct
XCT11BL	Cable Tie - 11" - 50lb	Black	100ct
XCT7BL	Cable Tie - 7.5" - 50lb	Black	100ct